



IEC 60034-1

2016/08
1033158130

INS CL. F		ΔT 80 K	SI	SF 1.00
V _L	Hz	kW	mm ² -1	A
30 Δ	50	22	1460	43.1
660 Y			1460	24.8
400 Δ	50	22	1465	41.0
690 Y			1465	23.8
415 Δ	50	22	1470	41.3
440 Δ			1760	42.1
460 Δ	60	25	1760	41.3

W2 U2 V2
U1 V1 W1
L1 L2 L3

W2 U2 V2
U1 V1 W1
L1 L2 L3

6311-C3
MOBIL TREX EM
183 Kg

6211-Z-C3
18 20000 h
IE1-90.2%


10331583



W21 **CE**

3 ~ 200L-04 IEC 60034-1
AMB 45°C 2016/02 1031330142

V	Hz	INS CL. F	$\Delta T_{80} K$	SI	SF 1.00
380 Δ				A	COS ϕ
660 Y	50	30	1470	59.6	0.84
400 Δ			1470	34.3	0.84
690 Y	50	30	1475	57.3	0.83
415 Δ	50	30	1475	33.2	0.83
440 Δ	50	30	1475	57.3	0.80
460 Δ	60	36	1765	60.7	0.85
			1470	59.5	0.83

W2 U2 V2
U1 V1 W1
L1 L2 L3

6312-C8 MOBIL POLYREX EW 254
6212-Z-C3 21 g 20000 h

ERE **RA**
38324 MOD.TEQUFOXK00003045





