

26-G28 ITEM 31-32



2nm

**Included In Package**

1 Navigation light, precabled with 2.5 meter sh  
marine grade cable, 2 Mounting screws (M6 \* 8  
mm), Installation guide

**Operating temperature**

-25°C to 55°C

**Mounting**

Vertical

**Materials**

Silver anodized aluminum 25μ, PMMA lens, A4  
stainless steel screws, Epoxy, Polyurethane

**Operating Voltage**

10-32VDC

**EAN**

5704438009097

**IP rating**

IP68

**Power draw (W)**

1,2

**UPC Code**

5704438009097

2.5m cable

**Current consumption (mA @ 12VDC)**

90

**Stock status**

Usually in stock

**Lead time**

1-2 weeks

**Current consumption (mA @ 24VDC)**

50

**Vessel size**

Under 12M,12-20M,20-50M

**Min. feed wire gauge**

0.5mm<sup>2</sup> AWG22

**Weight (Kg)**

0.38 Kg

**Weight (Oz)**

13.40 Oz

301-002

**Light Color**

Red

**Dimensions metric**

92,5 x 28 x 49,7

**Certification**

This Navigation Light is certified by DNV, the Declaration of conformity and the certificates found on [www.lopolight.com](http://www.lopolight.com) under Service & Support

**Intensity**

>5.4cd

**Dimensions imperial**

3.6" x 1.1" x 1.95"

**Approved to**

COLREG72,EN14744,IEC 60945,IACS  
E10,USCG,ABS,M.E.D.,DNV,LR

**Visibility**

2nm

**Included In Package**

Silver anodized aluminum 25 $\mu$ , PMMA lens, A4  
steel screws, Epoxy, Polyurethane

**Operating Voltage**

10-32VDC

**EAN**

5704438010437

**IP rating**

IP68

**Power draw (W)**

2,2

**UPC Code**

879343010430

**Connection**

2.5m cable

**Current consumption (mA @ 12VDC)**

163

**Stock status**

Usually in stock

**Current consumption (mA @ 24VDC)**

90

**Vessel size**

12-20M

**Min. feed wire gauge**

0.5mm<sup>2</sup> AWG22

**Weight (Kg)**

0.62 Kg

**Weight (Oz)**

21.87 Oz

Red, Green

### **Dimensions metric**

Ø92,5mm x 46mm

### **Certification**

This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on [www.lopolight.com](http://www.lopolight.com) under Service & Support

### **Intensity**

>5.4cd

### **Dimensions imperial**

Ø3.6" x 1.8"

### **Approved to**

COLREG72, EN14744, IEC 60945, IACS E10, USCG, ABS, M.E.D., DNV, LR

### **Visibility**

2nm

### **Included In Package**

1 Navigation light, precabled with 2.5 meter shielded marine grade cable

### **Operating temperature**

-25°C to 55°C

### **Mounting**

Horizontal

### **Materials**

Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel